



CLIENT :- MIT TRADE CO.,LTD
MODEL :- CUSTOMIZE
MEDIA - CLIENT TO SPECIFY
MOC - SS 316 All Contact Part
OPERATING PRESSURE - 20 Kg/cm2
DESIGN PRESSURE - 50 Kg/cm2
Torque - 7.5 N-m
OPERATING TEMP. °C - MAX 300 DEGREE
DESIGN TEMP. °C - 350 DEGREE
SYNCHRONOUS SPEED (rpm) : MAX 1440
<b>Note</b> - Material Of Conctruction All Contact Part in SS 316
<b>Note</b> - Material Of Conctruction All NON Contact Part in SS 304

				ALL DIMENSIONS ARE IN mm UNLESS OTHERWISE SPECIFIED. BREAK ALL CORNERS & SHARP EDGES.	
				MODEL :-Customize	MATL : SS 316
				NAME: Magnetic Drive Coupling	
				TOLERANCES FOR DIMENSIONS UNSPECIFIED TOLERANCES LINEAR ±0.1 ANGULAR ± 0.05	
				MACHINING FINE MACHINING GRINDING LAPPING	
				SCALE: NTS	
				DRG NO.: ND/MD-12344R1	
				SHEET : 1 OF 1	
<b>NANDODYNE ENGINEERING LLP.</b>					